

PRODUCT INFO

STUDSENSOR™ HD55

ZN-HD55



BARCODE: 042186660890

DIMENSIONS: 172mm x 72mm x 37mm
WEIGHT: 131g (without battery)
BATTERY TYPE: 9V alkaline, required
DEPTH: 1½ in. (38mm) deep

POSITION ACCURACY: Up to 19mm Depth: within 3mm

Up to 38mm Depth: within 5mm

WIREWARNING 90-250V at 50-60Hz within 152mm **POSITION ACCURACY:** of a hot unshielded wire in drywall.

WIREWARNING DEPTH: Up to 51mm deep.

OPERATING TEMP: -7° to 41°C **STORAGE TEMP:** -29° to 66°C

HUMIDITY: 5 - 90% RH (non-condensing) **WATER RESISTANCE:** Splash proof, not waterproof

Deep-Scanning Stud Finder with SpotLite® Pointer and WireWarning® Detection

The StudSensor™ HD55 deep-scanning stud finder boasts more design innovations by Zircon. Featuring an enhanced LCD display, it debuts a new Target Spotlight that illuminates on-screen when you've found the edge of a stud. Select from two stud scan modes to find the edges of wood and metal studs to securely anchor mirrors, shelves, and cabinets to the wall while also avoiding live AC electrical wiring.

FEATURES

- StudScan mode locates the edges of wood or metal studs up to ³/₄ in. (19 mm) deep
- DeepScan® mode doubles the scanning depth to
 1½ in. (38 mm) deep
- WireWarning® detection indicates the presence of live, unshielded AC electrical wiring up to 2 in.
 (51 mm) deep
- Zircon's patented "over-the-stud" indication alerts the user to start the scan in a new location if scanning begins over a stud
- Enhanced LCD display with Target Spotlight indicates approaching stud edge and illuminates when stud edge is detected
- SpotLite® Pointer shines an arrow-shaped light on the wall to clearly indicate the edge of the stud
- Translucent base and illuminated "V" marker groove for more accurate marking of stud edge location
- · Rubber handle for non-slip grip













