

PRODUCT INFO

MULTISCANNER® i65 ONESTEP®

ZN-165



BARCODE: 042186618785

DIMENSIONS: 158mm x 77mm x 34mm **WEIGHT:** 161g (without battery) **BATTERY TYPE:** 9V alkaline (not included)

DEPTH: StudScan: Up to 19mm

DeepScan: Up to 38mm

POSITION ACCURACY: Up to 19mm Depth: within 3mm for

center and 5mm for edge Up to 38mm Depth: within 6mm

WIREWARNING 90-250V at 50-60Hz within 152mm **POSITION ACCURACY:** of a hot unshielded wire in drywall.

WIREWARNING DEPTH: Up to 51mm deep.

OPERATING TEMP: -7° to 41°C STORAGE TEMP: -29° to 66°C

HUMIDITY: 5 - 90% RH (non-condensing) WATER RESISTANCE: Splash proof, not waterproof

Center Finding Stud Finder with Easyto-Read Display Screen

StudSensor™ i65 OneStep® quickly and easily locates the edges and center of wood and metal studs and joists behind walls, floors, and ceilings. Patented CenterVision® technology finds the center of studs in a single pass. Its easy-to-read display screen indicates directions, edges and center of studs, while WireWarning® detection indicates the presence of live AC voltage.

FEATURES

- StudScan mode locates the edges and center of wood or metal studs up to 3/4 in. (19 mm) deep
- DeepScan® mode doubles the scanning depth to 11/2 in. (38 mm)
- LCD display indicates direction, edges, and center
- Patented SpotLite® Pointing System and audio tone signals when the stud center is reached
- WireWarning® Detection indicates the presence of live, unshielded electrical wiring up to 2 in. (51 mm) deep
- ACT™ (Auto Correcting Technology) automatically corrects common user errors, such as when scanning begins over a stud













WIREWARNING® DETECTION

